

SBG...FLL SBG..SLL SBS..SLL

Type	Mounting Dimensions					Block Dimensions					Rail Size					Load capacity					Weight						
	Height(H)	W1	W2	Width(W)	Length(L)	Mounting tab hole(B×J)	Mounting tab hole(M×L)	L1	J1	K	T	Nipple Mounting Nipple(T1)	Nipple(N)	Width(W1)	Height(H1)	Pitch(F)	Bolt Hole(d×D×h)	G	Max.length Of rail Lomax	Dynamic C(kgf)	Satiny Co(kgf)	Stationary moment(kgf.M) MRO	Stationary moment(kgf.M) MPO	Stationary moment(kgf.M) MRO	bearing (kgf)	rail (kgf/M)	
SBG55SLL	80	10.5	22.5	100	201	75*95	M12*H8	156.1	30.55	69.5	18	PT1/8	22	16	53	45	120	16*23*20	30	4480	12130	18660	449	435	426	6	14.9
SBG45SLL	70	8	19.5	86	171	60*80	M10*H7	129.8	24.5	62	15	PT1/8	20.3	16	45	38	105	14*20*17	225	4450	8200	12954	264	251	248	3.8	10.9
SBG35SLL	55	7.5	17	70	135	50*72	M8*H2	105.8	16.9	47.5	10	M6*0.75	16.5	12	34	29	80	9*14*12	20	4440	5120	8310	136	144	141	2	6.3
SBG30SLL	45	5.5	15.5	60	120.5	40*60	M8*H0	93	16.5	39.5	8	M6*0.75	11.5	12	28	25	80	9*14*12	20	4440	3800	6375	80	86	85	1.2	4.5
SBG25SLL	40	5.2	12	48	102.5	35*50	M6*H8	78.6	14.3	35.5	8	M6*0.75	9.95	12	23	21.8	60	7*11*9	20	4480	2770	4680	48	54	53	0.8	3.14
SBG20SLL	30	3.6	11.5	44	90	32*36	M5*6	66.8	8.4	26.5	8	M6*0.75	4.45	12	20	17.5	60	6*9.5*8.5	20	3040	2170	3240	31	35	35	0.4	2.16
SBG65FLL	90	17.5	53.5	170	246	142*110	M16*H7	206.5	48.25	72.5	23	PT1/8	15	16	63	58.5	150	18*26*22	35	4390	19580	29170	834	850	830	14	21.3
SBG55FLL	70	10.5	43.5	140	201	116*95	M14*H7	156.1	30.55	59.5	17	PT1/8	12	16	53	45	120	16*23*20	30	4480	12100	18660	449	435	426	6.3	14.9
SBG45FLL	60	8	37.5	120	171	100*80	M12*H5	129.8	24.9	52	15	PT1/8	10.5	16	45	38	105	14*20*17	22.5	4450	8200	12950	264	251	248	3.8	10.9
SBG35FLL	48	7.5	33	100	135	82*62	M10*H21	105.8	21.9	40.5	13	M6*0.75	9.5	12	34	29	80	9*14*12	20	4440	5120	8310	136	144	141	2.1	6.3
SBG30FLL	42	5.5	31	90	120.3	72*52	M10*H18	93	20.5	36.5	12	M6*0.75	8.5	12	28	25	80	9*14*12	20	4440	3800	6370	80	86	85	1.4	4.5
SBG25FLL	36	5.2	23.3	70	102.5	57*45	M8*H6	78.6	16.8	31.5	10	M6*0.75	5.95	12	23	21.8	60	7*11*9	20	4480	2770	4680	48	54	53	0.81	3.14
SBG20FLL	30	3.6	21.3	63	90	53*40	M6*H0	66.8	13.4	26.5	9	M6*0.75	4.45	12	20	17.5	60	6*9.5*8.5	20	3040	2170	3240	31	35	35	0.57	2.16
SBG65SLL	90	17.5	28.5	126	246	76*120	M16*H20	206.5	43.25	72.5	23	PT1/8	15	16	63	58.5	150	18*26*22	35	4390	19580	29170	834	850	830	10.5	21.3