

# Single-row Four Point Contact Ball Slewing Bearings (Internal gear type)

| Designations   | Boundary Dimension [mm] |     |     | Bolt Hole Diameter [mm] |      |      |      |   |     | Weight [Kg] |
|----------------|-------------------------|-----|-----|-------------------------|------|------|------|---|-----|-------------|
|                | Da                      | Di  | إتش | La                      | Li   | na3) | ni3) | m | z   |             |
| I.505.20.00.C  | 518                     | 325 | 56  | 490                     | 375  | 8    | 12   | 5 | 67  | 27.5        |
| I.650.20.00.C  | 648                     | 444 | 56  | 620                     | 505  | 10   | 16   | 6 | 76  | 38          |
| I.750.20.00.C  | 748                     | 546 | 56  | 720                     | 605  | 12   | 18   | 6 | 93  | 45          |
| I.850.20.00.C  | 848                     | 648 | 56  | 820                     | 705  | 12   | 20   | 6 | 110 | 51.5        |
| I.950.20.00.C  | 948                     | 736 | 56  | 920                     | 805  | 14   | 20   | 8 | 94  | 61.5        |
| I.1050.20.00.C | 1048                    | 840 | 56  | 1020                    | 905  | 16   | 22   | 8 | 107 | 67.5        |
| I.1200.20.00.C | 1198                    | 984 | 56  | 1170                    | 1055 | 16   | 24   | 8 | 125 | 81.5        |